

Dated 02/12/2022 Printed on 02/12/2022

Revision nr. 4

Page n. 1/14 Replaced revision:3

## **PYREKILL 2.5**

# **Safety Data Sheet**

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name
PYREKILL 2.5
Surgical medicla device n°
20411

JFI: 5F10-J0AU-S003-W79G

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Emulsifiable concentrated insecticide with rapid killing and flushing action. Professional use.

Identified Uses Industrial Professional Consumer
Insecticides -

## Uses Advised Against

All uses other than those recommended

1.3. Details of the supplier of the safety data sheet

Name COLKIM S.r.l. Full address Via Piemonte, 50

District and Country 40064 OZZANO EMILIA (BO)

Italia

Tel. 051 / 799445 Fax 051 / 797555

e-mail address of the competent person

responsible for the Safety Data Sheet info@colkim.it

Supplier: COLKIM S.r.I. - Via Piemonte, 50 - 40064 OZZANO E. (BO)

## 1.4. Emergency telephone number

For urgent inquiries refer to 118 Contact a poison control center:

Nane	City	Address	Zip code	Phone
CAV "Osp. Pediatrico Bambino Gesù"	Roma	P.zza Sant`Onofrio, 4	00165	06 68593726
Az. Osp. Univ. Foggia	Foggia	V.le Luigi pinto, 1	71122	0881 732326
Az. Osp. "A. Cardarelli"	Napoli	Via A. Cardarelli, 9	80131	081 7472870
CAV Policlinico "Umbero I"	Roma	V.le del policlinico, 155	00161	06 49978000
CAV Policlinico "A. Gemelli"	Roma	Largo Agostino Gemelli, 8	00168	06 3054343
Az. Osp. "Careggi" U.O. Tossicologia Medica	Firenze	Largo Brambilla, 3	50134	055 7947819
CAV Centro Nazionale di Informazione Tossicologica	Pavia	Via Salvatore Maugeri, 10	27100	0382 24444
Osp. Niguarda Ca' Granda	Milano	P.zza Ospedale Maggiore,3	20162	02 66101029
Azienda Ospedaliera Papa Giovanni XXII	Bergamo	P.zza OMS, 1	24127	800883300
CAV centro antiveleni Verona	Verona	Piazzale Aristide Stefani,1	37126	800011858

# **SECTION 2. Hazards identification**



Revision nr. 4 Dated 02/12/2022 Printed on 02/12/2022 Page n. 2/14 Replaced revision:3

## **PYREKILL 2.5**

## 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin sensitization, category 1 H317 May cause an allergic skin reaction. Hazardous to the aquatic environment, chronic toxicity, H411 Toxic to aquatic life with long lasting effects.

category 2

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

#### Hazard pictograms:





Signal words: Warning

Hazard statements:

H317 May cause an allergic skin reaction. Toxic to aquatic life with long lasting effects. H411

Precautionary statements:

If medical advice is needed, have product container or label at hand. P101

P103 Read label before use. P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

Do not eat, drink or smoke when using this product. Avoid release to the environment. P273 P280 Wear protective gloves / eye protection / face protection. P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents / container according to national regulation

**Contains:** Chrysanthemum cinerariaefolium

## 2.3. Other hazards

P270

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

# **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:



Revision nr. 4 Dated 02/12/2022 Printed on 02/12/2022 Page n. 3/14 Replaced revision:3

# **PYREKILL 2.5**

Classification (EC) 1272/2008 (CLP) Identification x = Conc. %

**DIPROPYLENE GLYCOL** MONOMETHYL ETHER

INDEX  $9 \le x < 10.5$ Substance with a community workplace exposure limit.

EC 252-104-2 CAS 34590-94-8

REACH Reg. 01-2119450011-60 Chrysanthemum cinerariaefolium

INDEX - $2.5 \le x < 3$ Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Sens. 1 H317, Aquatic Acute 1

H400 M=1, Aquatic Chronic 1 H410 M=1

LD50 Oral: 1030 mg/kg, STA Inhalation vapours: 11 mg/l EC 289-699-3

CAS 89997-63-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

# **SECTION 4. First aid measures**

## 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHĂLATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

# 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

## 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 4/14
Replaced revision:3

## **PYREKILL 2.5**

circuit positive pressure compressed air breathing apparatus (BS EN 137).

## **SECTION 6.** Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

# 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

## **SECTION 8. Exposure controls/personal protection**

## 8.1. Control parameters

Regulatory References:

EU

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81 GBR United Kingdom EH40/2005 Workplace exposure limits

United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)
OEL EU Directive (EU) 2022/431: Directive (EU) 2019/1831: Directive (EU) 20

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2021

## DIPROPYLENE GLYCOL MONOMETHYL ETHER



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 5/14
Replaced revision:3

## **PYREKILL 2.5**

уре	Country	TWA/8h		STEL/15min		Remarks Observa		
		mg/m3	ppm	mg/m3	ppm			
LEP	ITA	308	50			SKIN		
VEL	GBR	308	50			SKIN		
DEL	EU	308	50			SKIN		
TLV-ACGIH			50					
Predicted no-effect concentr	ration - PNEC							
Normal value in fresh water				19	mg	g/l		
Normal value in marine wate	er			1,9	mç	g/l		
Normal value for fresh water	rsediment			70,2	mç	g/kg/d		
Normal value for marine wat	er sediment			7,02	mç	g/kg/d		
Normal value for water, intermittent release		190	mg	//				
Normai value for water, inter	millent release			190	mç	g/I		
Normal value for water, inter		DMEL		190	mę	g/I		
	ect level - DNEL / Effects on	DMEL		190	Effects on	g/I		
Health - Derived no-effe	ect level - DNEL /	DMEL Acute systemic	Chronic local	Chronic		Acute	Chronic local	Chronic systemic
Health - Derived no-effe	ect level - DNEL / Effects on consumers		Chronic local	Chronic systemic 36 mg/kg	Effects on workers		Chronic local	Chronic systemic
	ect level - DNEL / Effects on consumers			Chronic systemic	Effects on workers	Acute	Chronic local	
Health - Derived no-effe	ect level - DNEL / Effects on consumers		VND	Chronic systemic 36 mg/kg bw/d	Effects on workers	Acute		systemic
Health - Derived no-effe	ect level - DNEL / Effects on consumers Acute local		VND VND	Chronic systemic 36 mg/kg bw/d 37.2 mg/m3	Effects on workers	Acute	VND	systemic  308 mg/kg  283 mg/kg
Health - Derived no-effe	ect level - DNEL / Effects on consumers Acute local		VND VND	Chronic systemic 36 mg/kg bw/d 37.2 mg/m3	Effects on workers	Acute	VND VND	systemic 308 mg/kg 283 mg/kg
Health - Derived no-effe  Route of exposure  Oral  Inhalation  Skin  Chrysanthemum cinera Threshold Limit Value	ect level - DNEL / Effects on consumers Acute local	Acute systemic	VND VND	Chronic systemic 36 mg/kg bw/d 37.2 mg/m3 121 mg/kg bw/d	Effects on workers	Acute systemic	VND VND	systemic 308 mg/kg 283 mg/kg

Legend: (C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

## 8.2. Exposure controls

8.2.1 APPROPRIATE ENGINEERING CONTROLS Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50-100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge	1-2.5 m/s



Revision nr. 4 Dated 02/12/2022

Printed on 02/12/2022

Replaced revision:3

Page n. 6/14

## **PYREKILL 2.5**

(active generation into zone of rapid air motion) (200-500 f/min) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into 2.5-10 m/s zone of very high rapid air motion). (500-2000 f/min.)

Within each range the appropriate value depends on:

Within each range the appropriate value depends on:	
Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

#### 8.2.2 PERSONAL **PROTECTION**











#### Eye and protection

Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

## Skin protection

## See Hand protection below

#### Hands/feet protection

Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact
- chemical resistance of glove material
- glove thickness
- dexterity.

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- -When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.

-Contaminated gloves should be replaced.
As defined in ASTM F-739-96 in any application, gloves are rated as:

- Excellent when breakthrough time > 480 min.
- Good when breakthrough time > 20 min.
- Fair when breakthrough time < 20 min.
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 7/14
Replaced revision:3

# **PYREKILL 2.5**

	should always be taken into account to ensure selection of the most appropriate glove for the task.  Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:  -Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.  -Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.  Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	Overalls.P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.
Environmental exposure controls	Emissions from manufacturing processes, including those from ventilation equipment, should be controlled for compliance with environmental protection legislation. Product residues must not be discharged without control into wastewater or water courses.

# **SECTION 9. Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance Colour	liquid Giallo paglierino/trasparente	Method:OPPTS 830.6303 Method: OPPTS 830.6302
Odour	characteristic	Method: OPPTS 830.6304
Melting point / freezing point	not determined	Reason for missing data: Determination not necessary for safe use of the product
Initial boiling point	not determined	Reason for missing data Determination not necessary for safe use of the product
Flammability	not available	Reason for missing data: Determination not necessary for safe use of the product
Lower explosive limit	not determined	Reason for missing data: Determination not necessary for safe use of the product
Upper explosive limit	not determined	Reason for missing data: Determination not necessary for safe use of the product
Flash point	not determined	Reason for missing data: Determination not necessary for safe use of the product
Auto-ignition temperature	not determined	Reason for missing data: Determination not necessary for safe use of the product
Decomposition temperature	not applicable	Reason for missing data:The mixture is not self-reactive
pH	7-8	Method:OECD test 122
Kinematic viscosity	not applicable	Reason for missing data:does not apply to aerosols
Solubility	not determined	Reason for missing data: Determination not necessary for safe use of the product
Partition coefficient: n-octanol/water	not applicable	Reason for missing data: Not determinable for mixtures
Vapour pressure	not available	Reason for missing data: Determination not necessary for safe use of the product
Density and/or relative density	1,05	Method:OECD test 109
Relative vapour density	not determined	Reason for missing data: Determination not necessary for safe use of the product
Particle characteristics		not relevant because the product is an aerosol

## 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 10,00 % - 105,00 g/litre



Revision nr. 4

Dated 02/12/2022

Printed on 02/12/2022

Page n. 8/14

Replaced revision:3

# **PYREKILL 2.5**

VOC (volatile carbon)

5,67 % - 59,51 g/litre

# **SECTION 10. Stability and reactivity**

## 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Forms peroxides with: air.

#### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

#### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

May react violently with: strong oxidising agents.

#### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

DIPROPYLENE GLYCOL MONOMETHYL ETHER

Avoid exposure to: sources of heat. Possibility of explosion.

#### 10.5. Incompatible materials

Information not available

## 10.6. Hazardous decomposition products

Information not available

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 9/14
Replaced revision:3

## **PYREKILL 2.5**

#### Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l ATE (Oral) of the mixture: > 2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

DIPROPYLENE GLYCOL MONOMETHYL ETHER

 LD50 (Dermal):
 9510 mg/kg Coniglio

 LD50 (Oral):
 5000 mg/kg Ratto

 LC50 (Inhalation vapours):
 3,35 mg/l/4h Ratto

Chrysanthemum cinerariaefolium

 LD50 (Dermal):
 > 2000 mg/kg CONIGLIO

 LD50 (Oral):
 1030 mg/kg RATTO

 LC50 (Inhalation vapours):
 2,3 mg/l/4h RATTO

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 10/14
Replaced revision:3

# **PYREKILL 2.5**

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

## **ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

# **SECTION 12. Ecological information**

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

## 12.1. Toxicity

Chrysanthemum cinerariaefolium

LC50 - for Fish 0,0052 mg/l/96h EC50 - for Crustacea 0,012 mg/l/48h

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

 LC50 - for Fish
 10000 mg/l/96h

 EC50 - for Crustacea
 1919 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 6999 mg/l/72h

 Chronic NOEC for Crustacea
 0,5 mg/l

## 12.2. Persistence and degradability

DIPROPYLENE GLYCOL MONOMETHYL

**ETHER** 

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

## 12.3. Bioaccumulative potential

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

Partition coefficient: n-octanol/water 1,01

# 12.4. Mobility in soil

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

Partition coefficient: soil/water 0,28

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

## 12.6. Endocrine disrupting properties



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 11/14
Replaced revision:3

## **PYREKILL 2.5**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

#### 14.1. UN number or ID number

ADR / RID, IMDG, IATA: 3082

ADR / RID: In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not

submitted to ADR provisions.

IMDG: In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or

5L, is not submitted to IMDG Code provisions.

IATA: In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to

IATA dangerous goods regulations.

## 14.2. UN proper shipping name

ADR / RID: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Chrysanthemum cinerariaefolium)

IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Chrysanthemum cinerariaefolium)

IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Chrysanthemum cinerariaefolium)

#### 14.3. Transport hazard class(es)

ADR / RID: Class: 9 Label: 9

IMDG: Class: 9 Label: 9

IATA: Class: 9 Label: 9



# 14.4. Packing group

ADR / RID, IMDG, IATA:

# 14.5. Environmental hazards



Revision nr. 4 Dated 02/12/2022 Printed on 02/12/2022 Page n. 12/14 Replaced revision:3

## **PYREKILL 2.5**

ADR / RID: Environmentally

Hazardous

IMDG: Marine Pollutant

IATA: Environmentally

Hazardous



## 14.6. Special precautions for user

ADR / RID: HIN - Kemler: 90 Limited Tunnel restriction Quantities: 5

code: (-)

964

964

IMDG: EMS: F-A, S-F Limited

Special provision: -

Quantities: 5

IATA: Cargo: Maximum Packaging quantity: 450 instructions:

Pass.: Maximum Packaging quantity: 450 instructions:

Special provision: A97, A158,

A197, A215

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15. Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>

3 Point

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None



Revision nr. 4
Dated 02/12/2022
Printed on 02/12/2022
Page n. 13/14
Replaced revision:3

## **PYREKILL 2.5**

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

This safety data sheet contains one or more Exposure Scenarios in an integrated form. Contents have been included in sections 1.2, 8, 9, 12, 15 and 16 of this safety data sheet.

## **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4

Skin Sens. 1 Skin sensitization, category 1

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H302 Harmful if swallowed.
H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- · CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization



Revision nr. 4 Dated 02/12/2022 Printed on 02/12/2022 Page n. 14/14

Replaced revision:3

## **PYREKILL 2.5**

INDEX: Identifier in Annex VI of CLP LC50: Lethal Concentration 50%

LD50: Lethal dose 50%

OEL: Occupational Exposure Level

PBT: Persistent bioaccumulative and toxic as REACH Regulation

PEC: Predicted environmental Concentration

PEL: Predicted exposure level

PNEC: Predicted no effect concentration

REACH: Regulation (EC) 1907/2006

RID: Regulation concerning the international transport of dangerous goods by train

TLV: Threshold Limit Value

TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.

TWA: Time-weighted average exposure limit

TWA STEL: Short-term exposure limit

VOC: Volatile organic Compounds

vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament

2. Regulation (EC) 1272/2008 (CLP) of the European Parliament

3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)

Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament

5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament

6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament

8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament

9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament

11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament

12. Regulation (EU) 2016/1179 (IX Atp. CLP)

13. Regulation (EU) 2017/776 (X Atp. CLP)

14. Regulation (EU) 2018/669 (XI Atp. CLP)

15. Regulation (EU) 2019/521 (XII Atp. CLP)

16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)

17. Regulation (EU) 2019/1148

18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)

19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)

20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP) 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

The Merck Index. - 10th Edition
 Handling Chemical Safety

INRS - Fiche Toxicologique (toxicological sheet)

Patty - Industrial Hygiene and Toxicology

N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

IFA GESTIS website

ECHA website

Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a quarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 06 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.